

35 SET (FSM) 22" in ground, cap stamped:
Raised rock mound 3 1/2" dia. 8" high.

T6N R24E
E 1/16 • S27
LS 3848
1990

36 SET (FSM) 21" in ground, cap stamped:
Raised rock mound 4' dia. by 9" high.

T6N R24E
E 1/16
C---C
S27
LS 3848
1990

37 SET standard Forest Service 3 1/4" Aluminum disc in
NW corner of granite slab, surface 2 1/2' x 4 1/2'. Disc stamped:
From which bear:

T6N R24E
NE 1/16 • S27
LS 3848
1990

38 SET (FSM) 19" in side hill. Cap stamped:
Raised rock mound 5' dia. by 11" high.

T6N R24E
N 1/16 C
S27
LS 3848
1990

39 SET (FSM) 23" in ground. Cap stamped:
Raised rock mound 3' dia. by 7" high.
From which bear:

T6N R24E
W 1/16 • S27
LS 3848
1990

40 SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 4 1/5' dia. by 8" high.
From which bears:

T6N R24E
NW 1/16 • S27
LS 3848
1990

1" IP tagged RCE10467 per (R3) S.61°12'56"W., 11.2'

41 SET (FSM) 21" in ground. Cap stamped:
Raised rock mound 4' dia. by 9" high.
From which bears:

T6N R24E
N 1/16
S28 1/2 S27
LS 3848
1990

42 SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 4' dia. by 8" high.
1" IP tagged RCE10467 per (R3) S.60°12'56"W., 21.60'

T6N R24E
S 1/16
S22 1/2 S23
LS 3848
1990

43 FOUND 5/8" Rebar tagged RCE30029 S.72°32'17"E., 0.36' from point for corner
(No reference for this monument).

T6N R24E

SET (FSM) 9" into rocky hillside at point for corner. Cap Stamped:
Deposit 5/8" Rebar along west side of monument.
Raised rock mound 6' dia. by 21" high.

E 1/16
C---C
S22
LS 3848
1990

44 SET (FSM) 20" in ground. Cap stamped:
Raised rock mound 3' dia. by 10" high.

T6N R24E
SE 1/16 • S22
LS 3848
1990

45 SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 3' dia. by 8" high.

T6N R24E
S 1/16 C
S22
LS 3848
1990

46 SET (FSM) 20" in ground. Cap stamped:
Raised rock mound 5' dia. by 10" high.

T6N R24E
C 1/4 • S22
LS 3848
1990

47 SET (FSM) 21" in ground. Cap stamped:
Raise rock mound 5' dia. by 9" high.

T6N R24E
N 1/16
S22 1/2 S23
LS 3848
1990

48 FOUND 1" IP tagged RCE27104 per (R7) S.04°10'11"E., 0.35' from point for corner.
SET (FSM) 15" in ground at point for corner. Cap stamped:
Deposit 1" x 1.7" IP along south side of monument.
Raise rock mound 5' dia. by 15" high.

T6N R24E
N 1/16
S21 1/2 S22
LS 3848
1990

49 SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 4' dia. by 8" high.
From which bear:

T6N R24E
W 1/16
C---C
S10
LS 3848
1990

2" IP tagged RCE10467 per (R5) N.24°34'00"W., 25.64'

50 SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 3 1/2' dia. by 8" high.
From which bear:

T6N R24E
NW 1/16 • S10
LS 3848
1990

2" IP tagged RCE10467 per (R5) N.25°02'14"W., 12.37'

51 SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 4' dia. by 8" high.
From which bear:

T6N R24E
N 1/16
S9 1/2 S10
LS 3848
1990

2" IP tagged RCE10467 per (R5) N.34°06'43"W., 18.16'

52 SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 42" dia. by 8" high.
From which bear:

T6N R24E
N 1/16 C
S28
LS 3848
1991

2" IP tagged RCE10467 per (R3) S.76°57'28"W., 24.39'

53 SET (FSM) 23" in ground. Cap stamped:
Raised rock mound 3' dia. by 7" high.
From which bears:

T6N R24E
NW 1/16 • S28
LS 3848
1991

1" IP tagged RCE10467 per (R3) S.77°20'13"W., 11.99'

54 SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 42" dia. by 8" high.
From which bear:

T6N R24E
W 1/16
C---C
S28
LS 3848
1991

1" IP tagged RCE10467 per (R3) S.83°05'51"W., 8.08'

55 SET (FSM) 20" in ground. Cap stamped:
Raised rock mound 3' dia. by 10" high.
From which bears:

T6N R24E
NE 1/16 • S21
LS 3848
1990

1" IP tagged RCE27104 per (R7) N.88°13'19"W., 3.87'

56 FOUND 1" IP tagged RCE10467 per (R4) S.21°51'38"E., 0.24' from point for corner
SET (FSM) 20" in ground at point for corner. Cap stamped:
Deposit 1" x 24" IP along south side of monument. Raised
rock mound 3 1/2' dia. by 10" high.

T6N R24E

E 1/16 S16
S21
LS 3848
1990

57 SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 4' dia. by 8" high.
From which bear:

T6N R24E
C 1/4 • S21
LS 3848
1991

1" IP tagged RCE27104 per (R7) N.89°20'42"W., 15.90'

58 SET (FSM) 22" in side hill. Cap stamped:
Raised rock mound 4' dia. by 8" high.
From which bears:

T6N R24E
W 1/16
C---C
S21
LS 3848
1991

1" IP tagged RCE2704 per (R7) S.88°47'47"W., 7.94'

59 SET (FSM) 21" in ground. Cap stamped:
Raised rock mound 3' dia. by 9" high.
From which bears:

T6N R24E
SW 1/16 • S21
LS 3848
1991

1" IP tagged RCE10467 per (R3) S.78°18'36"W., 11.98'

60 FOUND 1" IP tagged RCE10467 per (R3) S.66°39'49"E., 0.21' from point for corner,
SET (FSM) 22" in ground at point for corner. Cap stamped:
Deposit 1" x 24" IP along north side of monument.
Raised rock mound 40" dia. by 8" high.

T6N R24E
S 1/16
S20 1/2 S21
LS 3848
1991

61 FOUND 1" IP tagged RCE10467 per (R4) S.50°48'41"W., 0.55' from point for corner.
SET (FSM) 18" in rock at point for corner. Cap stamped:
Deposit 1" x 24" IP along south side of monument.
Raised rock mound 5' dia. by 12" high.

T6N R24E
E 1/16
C---C
S16
LS 3848
1990

62 SET standard Forest Service 3 1/4" aluminum disc on steep east facing boss
extusion. Disc stamped:
From which bear:
Track in rock and tog (RCE 10467) per (R4) S.53°W., 0.18'

63 FOUND 1" IP in rock mound per (R4) S.71°35'54"W., 0.17' from point for corner
SET (FSM) 21" in ground at point for corner. Cap stamped:
Deposit 1" x 24" IP along north side of monument.
Raised rock mound 3 1/2' dia. by 9" high.

64 FOUND 1" tagged RCE10467 per (R4) N.87°44'44"E., 0.19' from point for corner
SET (FSM) 22" in ground at point for corner. Cap stamped:
Deposit 1" x 24" IP along north side of monument.
Raised rock mound 4' dia. by 8" high.

65 FOUND 1" IP tagged RCE10467 per (R4) N.75°38'25"E., 0.36' from point for corner
SET (FSM) 22" in ground at point for corner. Cap stamped:
Deposit 1" x 24" IP along north side of monument.
Raised rock mound 4' dia. by 8" high.

66 FOUND 2" IP stamped 1/4 COR 9-16 RCE10467 in imbedded 3' dia. rock mound
Accepted as point for corner.

SET (FSM) 20" in ground in place of 2" IP. Cap stamped:
Deposit 2" IP along east side of monument. Rebuilt
rock mound 3' dia. by 10" high. From which bear:
JP stump ±44" S.55E., 118.9'. (R1) YP 36" S.55E., 117.5'
NEW BT: J 8" DBH N.26°W., 39.5', scribed "1/4 S9 BT", tagged LS 3848

MONUMENT DESCRIPTION LEGEND



(R1)	1878 GOVERNMENT SURVEY	
(R2)	1925 GLO RESURVEY	
(R3)	1 PM 66	
(R4)	1 PM 80	
(R5)	1 RS 31	
(R7)	1 RS 98	
(GLOM)	STANDARD 1" X 36" IP GENERAL LAND OFFICE SURVEY MONUM	
(FSM)	WITH 2 1/2" BRASS CAP. (2" x 36" IP at Section corner)	
	STANDARD 2" X 30" U.S. FOREST SERVICE ALUMINUM-MAGNETIT	
	SURVEY MONUMENT WITH 3 1/4" ALUMINUM CAP.	
DBH	DIAMETER BREAST HIGH (4 1/2' ABOVE HIGH SIDE GROUND LE	
BT	BEARING TREE	LP
RT	REFERENCE TREE	MM
A	ASPEN	WBP
C	COTTONWOOD	WF
J	JUNIPER	YP
JP	JEFFREY PINE	IP
		IRON PIPE

RECORD OF SURVEY No. 1

SECTIONS 9,10,16,20,21,22,27,&
TOWNSHIP 6 NORTH, RANGE 24 EAS
COUNTY OF MONO STATE OF CAL

JAMES NICKLOS (LS 3848) & ASSOCIATES